

**NAME**

scriptrouted – Network measurement server

**SYNOPSIS**

**scriptrouted** [**--help**] [**--version**] [**--config=<configuration file>**] [**--port=<service port>**] [**--disable-daemon**] [**--verbose**]

**DESCRIPTION**

Scriptroute is a system for distributed network measurement and debugging. The scriptroute daemon provides an interface for user-owned processes to send measurement traffic and receive responses.

**OPTIONS**

**--help, -h**

Show a summary of command line options

**--version, -V**

Show the scriptroute daemon version.

**--config, -c**

Use the specified configuration file. Be sure to use this option, as the default configuration may not be exactly what you want, and will not publish the correct administrator's address.

**--port, -p**

Provide service on a port other than 3356. This is not well supported.

**--disable-daemon, -d**

Run in the foreground, don't turn into a daemon. Only really useful for debugging.

**--verbose, -v**

Print more debugging messages than normal. Such additional messages will go into syslog under daemon.debug.

**BUGS**

Send bug reports or suggestions to <bugs@scriptroute.org>.

**FILES**

*/etc/scriptroute/scriptroute.conf*

Scriptroute configuration file.

**AUTHOR**

Neil Spring <nspring@cs.washington.edu>

**SEE ALSO**

**srinterpreter(1)**